



SIGNWIRE spec 981401XX

(Please see 1.3 below for color selection)



Ballastwire : 14 AWG

USED FOR FLUORESCENT PRIMARY & SECONDARY BALLAST WIRE



Type: This cable consists of one 14 AWG stranded bare copper conductor.

1.0 SPECIFICATIONS

1.1 Conductor:

- 1.1.1 Material: Bare Copper
- 1.1.2 Size: 14 AWG
- 1.1.3 Stranding: 19 Strand


1.2 Insulation:

- 1.2.1 Material: PVC
- 1.2.2 Wall Thickness: .031" nom.
- 1.2.3 O.D.: .134" nom.

1.3 Insulation/Jacket Color: (XX):

- 1.3.1 *Primary*
 - BK - Black
 - WH - White
- 1.3.2 *For Primary & Secondary*
 - GN - Green
- 1.3.3 *For Secondary*
 - RD - Red
 - BL - Blue
 - YW - Yellow
 - OR - Orange
 - BN - Brown
 - BLWH - Blue w/White Stripe
 - ORBK - Orange w/Black Stripe

1.4 Surface Print:

- 1.4.1 "PAIGE BALLAST WIRE 981401XX E355846 14 AWG (UL) MTW OR  AWM 1230/1015 600V 105°C OR AWM 1032 1000V 90°C VW-1 OIL RES I SUN RES AND CSA LL226471 AWM I/II A/B 105/ FT1 OR TEW 105°C ROHS COMPLIANT" (Sequential footage markers)

1.5 Electricals:

- 1.5.1 DC Resistance per Conductor: 2.53 ohms/M ft. nom. @ 20°C

1.6 Put-Ups:

- 1.6.1 4 x 500 ft. (2,000 ft. per carton)